

AIR40 TWIN CYLINDER AIR COMPRESSOR + INFLATION KIT



MAX AIR
FLOW RATE



MAX PRESSURE
300PSI



THERMAL
PROTECTION

The Oricom AIR40 is a high-performance twin cylinder air compressor, delivering quick inflation with a 300PSI max pressure and 130L/min max air flow rate, perfect for 4WDs and off-road vehicles. Featuring a durable air filter, automatic shut-off, and thermal protection, for safe, reliable inflation.



AUTO PRESSURE
CUT OFF



AIR-X
SERIES

3

YEAR
WARRANTY

oricom

100% AUSSIE OWNED

AIR40 TWIN CYLINDER AIR COMPRESSOR + INFLATION KIT

130L/min
MAX AIR
FLOW RATE

300PSI
MAX PRESSURE

**THERMAL
PROTECTION**

KEY FEATURES

- **Max Pressure of 300 PSI** – High pressure capability for larger tyres and tough inflating jobs.
- **High Flow Rates at Various Pressures** – Offers a consistent, high flow rate even at different pressure settings, enhancing performance and speed.
- **Air Flow Rate of 130L/min (0 PSI)** – Rapid inflation even at lower pressures, reducing downtime.
- **Thermally Protected Motor** – Prevents overheating during extended use, ensuring long-term durability.
- **Washable Air Filter** – Reduces maintenance by allowing easy cleaning and reusability.
- **Automatic Shut-Off Pressure Switch (120-150 PSI)** – Safeguards your tyres and compressor by preventing overinflation.
- **Quick Connect NPT 1/4" Connector** – Efficient power usage that reduces strain on the vehicle's electrical system.
- **Pressure Cut-Out Switch (120PSI On/160PSI Off)** – Enhances safety and ensures the compressor does not overwork, prolonging its lifespan.
- **Max Working Pressure of 150 PSI** – Ensures reliable performance for large vehicle tyres even in demanding situations.

TECHNICAL SPECIFICATION

Number of Cylinders	2
Cylinder Diameter (Bore)	40mm
Voltage	12-13.8VDC
Current Draw Under Load	62A
Current Draw No Load	35A
In line Fuse Supplied	40A
Washable Air Filters	Yes
Max Pressure	300PSI
Max Working Pressure	150PSI
Duty Cycle	Working 45mins - Rest 20mins
Air Flow Under Load	108L/min (40PSI)
Air Flow Rates	130 L/min (0PSI) 112 L/min (29PSI)
Automatic Shut-off	120-150psi pressure switch
Pressure Cutout Switch	Cuts out automatically when 120-150psi pressure reached
Motor Thermal Protection	Yes
Connection to Battery	Wiring loom
Hose Length	6m
Hose Connector Type	NPT 1/4" Quick Connect
Product Dimensions (cm)	29x24.5x12
Weight	10.2kg
Warranty	3 Years

PACK INCLUDES

- 1 x Twin Cylinder Air Compressor
- 2 x Washable Air Filters
- 1 x Switch
- 2 x Wiring Looms
- 1 x 6m Inflation Hose with 1/4" NPT quick connect fitting
- 1 x Digital Tyre Gauge
- Required Mounting Hardware



oricom.com.au

Oricom® is the registered trade mark of Oricom Holdings Pty Ltd. All other trade marks are trade marks of their respective owners. Due to continued product development, the product may differ slightly to that illustrated in this brochure.

oricom
100% AUSSIE OWNED