

TSE10-2 TYRE PRESSURE

MONITORING SYSTEM TWIN PACK OF EXTERNAL SENSORS

This Tyre Pressure monitoring twin pack of external sensors can be used with the Oricom TP510 system, which allows up to 10 sensors to be connected simultaneously.

12 MONTH
WARRANTY

TECHNICAL SPECIFICATION

SENSOR

| | |
|-----------------------|-------------------------|
| Operating frequency | 433.92MHz \pm 0.05MHz |
| Operating voltage | 2.3 ~ 3.3V |
| Operating current | \leq 12mA |
| Static current | \leq 0.5uA |
| Operating temperature | -20°C ~ +80°C |
| Storage temperature | -40°C ~ +80°C |
| Battery model | CR1632 |

DISPLAY

| | |
|---------------------------|------------------------------|
| Operating frequency | 433.92MHz \pm 0.05MHz |
| Operating current | \leq 3.5mA |
| Static current | \leq 45uA |
| Operating voltage | 2.6 ~ 3.6V |
| Operating temperature | -20°C ~ +70°C |
| Storage temperature | -40°C ~ +95°C |
| Built-in battery capacity | 500mAh |
| Charging temperature | -10°C ~ 65°C |
| Solar charging current | \geq 15mA (at 5500LX 25°C) |
| USB charging current | \leq 70mA |

