5 WATT UHI CB RADIO

DIE CAST METAL CHASSIS





OUR CONNECTION

The First Nation people understand the importance of connection to the land and water ways because they have lived off the land for thousands of years. Warriors have hunted and gathered for families to survive. Their song lines and the dreaming are their spiritual guides. They value the land, which provides for them in return.

THE ARTIST

Daniel Evans is an accomplished Indigenous artist, mentor, and fitness coach who has made significant contributions to the Australian Indigenous community. He is the founder of Walkabout Warriors, a mentorship program that focuses on building better mindsets and promoting resilient mental health.



Royalties go back to the artist and his community Walkabout Warriors.







5 WATT UHF CB RADIO

DIE CAST METAL CHASSIS







- Compact radio with large backlit LCD display
- Switchable RF power (high: 5 watt, low: 1 watt)
- 3 Programmable instant channel buttons
- 80 channels[†]
- High capacity Lithium-ion battery with up to 30hrs operating time[^]
- Fast charge technology supplied with 240v and 12v adaptors
- Open/instant/priority scan
- Die cast metal chassis
- Duplex (range extender)
- Signal monitoring
- Triple watch
- Audio scrambler
- Squelch tail on/off
- 38 CTCSS and 104 DCS codes
- Rotary volume control
- 2.5mm jack socket with locking screw for optional accessories
- Designed, engineered & made in Korea
- 3 year warranty excludes battery*

TECHINICAL SPECIFICATION - GENERAL

Compliance	AS/NZS 4365:2011 and NZS2772.1
Frequency Range TX/RX	476.425 - 477.4125 MHz
Number of Channels	80 UHF CB (75 Usable)†
Channel Spacing TX/RX	12.5KHz
Channel Spacing RX	12.5KHz
Operating modes	Simplex, Duplex
Scanning Speed	150msec/per channel
Antenna Impedance	50 Ohm
Battery Capacity	7.4V, 2600mAh Li-ionBattery. Operating time up to 20hrs on High TX power, 30hrs on Low TX power with antenna.
Frequency Stability	+/- 2.5ppm



RF Output Power	5 Watts max.
Modulation	FM
Maximum Deviation	+/- 2.5KHz
Spurious Emissions	Less than-30dBm
TX Frequency Response	+1 to -3dB of 6dB/octave from 300Hz to 3000Hz
Audio Signal to Noise Ratio	More than 35dB

RECEIVER

Circuit Type	Direct conversion by Single DSP chip
Intermediate Frequencies	IF = 137KHz
Sensitivity	Less than -122dBm at 12dB SINAD
Selectivity	More than 70dB
Intermodulation Immunity	More than 70dB
Spurious Response Immunity	More than 60dB
Audio Signal to Noise Ratio	More than 50dB
Receive Frequency Response	+1 to -3dB of 6dB/octave from 300Hz to 3000Hz
Conducted Spurious Emissions	Less than -57dBm at 9KHz

OPTIONAL ACCESSORIES

- Speaker Mic (SPKMIC5000)
- Throat Mic (THMIC5000)
- Compact Speaker with In-line Mic (EBVOX5000)
- 1dBi Magnetic Roof Mount Antenna & Adaptor for portable mounting (ANU025C)
- * 3 year warranty excludes battery

† This 80 channel narrowband radio has a total of 75 usable voice channels. Channels 22 and 23 are used for Telemetry and Telecommand, voice communications are not allowed on these channels. Channel 61, 62 and 63 are guard channels and are not available for use.



